

WINDFORCE

TBR TIRES



***ENJOY YOUR TRIPS WITH
WINDFORCE TYRES***

CATALOGUE 2018



PATTERN SUMMARY



LONG HAUL



WD2000



WD2020



WD2062+



WD3080



WH1000



WH1020



WH1022



WH3060



REGIONAL



WD2020



WD2068



WD2060



WD2048



WA1060



WA1068



WA1088



WA1062+



ON & OFF



WA1060



WA1062+



WA1068



WA1066



WD2066



WT3030



WD2088



WD2068



WT3000

- ① Application: Trailer Wheel for regional use.
- ② Suitable for high and medium speed on good road surface with excellent anti-skid-side character and drainage performance.
- ③ Excellent loading capacity, Low rolling resistance, Low noise.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel



WH1020

- ① Application: Steer Wheel for long distance, also can be used on Trailer Wheel.
- ② Suitable for high speed on good road surface application, with excellent durability, anti-side wear performance.
- ③ Longer mileage, Lower noise, Good stone-picking prevention.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel












WD2020

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.














- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel












M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
T3000R03	215/75R17.5 135/133J	18	12.0	15.0	6.00	TL	Trailer	Highway	D	C		72
T3000R04	235/75R17.5 143/141J	18	12.5	15.8	6.75	TL	Trailer	Highway	D	C		72
T3000R06	225/70R19.5 128/126M	14	12.5	15.5	6.75	TL	Trailer	Highway	D	C		72
T3000R07	245/70R19.5 136/134M	16	12.5	15.8	7.50	TL	Trailer	Highway	D	C		72
T3000R08	265/70R19.5 143/141J	18	12.5	15.8	7.50	TL	Trailer	Highway	D	C		72
T3000R09	285/70R19.5 150/148J	18	13.0	16.0	8.25	TL	Trailer	Highway	D	C		72

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
H1020R26	* 8.5R17.5 121/120L	16	12.0	15.0	6.00	TL	All	Highway	-	-	-	-
H1020R27	* 9.5R17.5 131/129L	16	12.5	15.8	6.75	TL	All	Highway	-	-	-	-
H1020R02	215/75R17.5 127/124M	16	12.0	15.0	6.00	TL	All	Highway	D	B		72
H1020R03	* 225/75R17.5 129/127M	16	12.0	15.0	6.75	TL	All	Highway	D	B		72
H1020R04	235/75R17.5 132/130M	16	12.5	15.8	6.75	TL	All	Highway	D	B		72
H1020R05	* 245/70R17.5 136/134M	16	12.5	15.8	7.50	TL	All	Highway	D	B		72
H1020R06	225/70R19.5 128/126M	14	12.5	15.5	6.75	TL	All	Highway	D	B		72
H1020R07	245/70R19.5 136/134M	16	12.5	15.8	7.50	TL	All	Highway	D	B		72
H1020R08	265/70R19.5 140/138M	16	12.5	15.8	7.50	TL	All	Highway	D	B		72
H1020R09	285/70R19.5 146/144M	16	13.0	16.0	8.25	TL	All	Highway	D	B		72

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2020R26	* 8.5R17.5 121/120L	16	15.0	19.0	6.00	TL	Drive	Highway	-	-	-	-
D2020R27	* 9.5R17.5 131/129L	16	15.0	19.0	6.75	TL	Drive	Highway	-	-	-	-
D2020R02	215/75R17.5 127/124M	16	15.0	19.0	6.00	TL	Drive	Highway	D	C		74
D2020R03	* 225/75R17.5 129/127M	16	15.0	19.0	6.75	TL	Drive	Highway	D	C		74
D2020R04	235/75R17.5 132/130M	16	15.5	19.6	6.75	TL	Drive	Highway	D	C		74
D2020R05	* 245/70R17.5 136/134M	16	15.5	19.6	7.50	TL	Drive	Highway	D	C		74
D2020R06	225/70R19.5 128/126M	14	15.5	19.6	6.75	TL	Drive	Highway	D	C		74
D2020R07	245/70R19.5 136/134M	16	15.5	19.6	7.50	TL	Drive	Highway	D	C		74
D2020R08	265/70R19.5 140/138M	16	15.5	19.6	7.50	TL	Drive	Highway	D	C		74
D2020T09	285/70R19.5 146/144M	16	16.0	20.0	8.25	TL	Drive	Highway	D	C		74

* New Developing Sizes

The labelling information is subject to change without notice.



WT3000

- ① Application: Trailer Wheel for regional use.
- ② Suitable for high and medium speed on good road surface with excellent anti-skid-side character and drainage performance.
- ③ Excellent loading capacity, Low rolling resistance, Low noise.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel



WH1020

- ① Application: Steer Wheel for long distance, also can be used on Trailer Wheel.
- ② Suitable for high speed on good road surface application, with excellent durability, anti-side wear performance.
- ③ Longer mileage, Lower noise, Good stone-picking prevention.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel









WD2020

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.
















- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel











M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
T3000R10	275/70R22.5 148/145M	16	14.5	18.4	8.25	TL	Trailer	Highway	D	C		72
T3000R02	385/55R22.5 160L	20	15.5	19.6	12.25	TL	Trailer	Highway	D	C		73
T3000R03	385/65R22.5 160L	20	15.5	19.6	11.75	TL	Trailer	Highway	D	C		73

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
H1020R25	11R22.5 148/145M	16	14.5	18.4	8.25	TL	All	Highway	D	B		72
H1020R14	295/75R22.5 146/143M	16	15.5	19.6	9.00	TL	All	Highway	D	B		72
H1020R22	11R24.5 149/146M	16	14.5	18.4	8.25	TL	All	Highway	-	-	-	-
H1020R24	285/75R24.5 147/144M	16	15.5	19.6	8.25	TL	All	Highway	-	-	-	-
H1020R26	255/70R22.5 140/137M	16	14.0	17.6	7.50	TL	All	Highway	D	B		72
H1020R10	275/70R22.5 148/145M	16	14.5	18.4	8.25	TL	All	Highway	D	B		72
H1020R15	295/80R22.5 152/149M	18	15.5	19.6	9.00	TL	All	Highway	D	B		73
H1020R17	315/70R22.5 154/150M	20	15.0	19.0	9.00	TL	All	Highway	D	B		73
H1020R18	315/80R22.5 156/150M	20	15.5	19.6	9.00	TL	All	Highway	D	B		73
H1020R16	12R22.5 152/149M	18	15.5	19.6	9.00	TL	All	Highway	D	B		73
H1020R19	385/55R22.5 160L	20	15.5	19.6	12.25	TL	All	Highway	D	B		73
H1020R20	385/65R22.5 160L	20	15.5	19.6	11.75	TL	All	Highway	D	B		73

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2020R12	11R22.5 148/145M	16	20.0	25.2	8.25	TL	Drive	Highway	D	C		74
D2020R14	295/75R22.5 146/143K	16	20.0	25.2	9.00	TL	Drive	Highway	D	C		75
D2020R22	* 11R24.5 149/146K	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-
D2020R23	* 285/75R24.5 147/144K	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-
D2020R10	275/70R22.5 148/145M	16	18.0	22.8	8.25	TL	Drive	Highway	D	C		74
D2020R15	295/80R22.5 152/149M	18	20.0	25.2	9.00	TL	Drive	Highway	D	C		75
D2020R17	315/70R22.5 154/150M	20	20.0	25.2	9.00	TL	Drive	Highway	D	C		75
D2020R18	315/80R22.5 156/150M	20	20.0	25.2	9.00	TL	Drive	Highway	D	C		75
D2020R16	12R22.5 152/149M	18	20.0	25.2	9.00	TL	Drive	Highway	D	C		75

* New Developing Sizes

The labelling information is subject to change without notice.



WINDFORCE



WA1060

- 1 Application: All Position Wheels for On/Off use.
- 2 Mixed pattern, Suitable for mixed road surface and relatively poor road condition with sideslip resistance.
- 3 Excellent crack & tear resistance, High speed, Long mileage.



- Standard Wheel
- Permitted Wheel
- Prohibited Wheel



WD2060

- 1 Application: Drive Wheel for On/Off Road use.
- 2 Suitable for mix road use and relatively poor road condition with excellent traction character.
- 3 Excellent load capability, Longer mileage, Good anti-wearing.



- Standard Wheel
- Permitted Wheel
- Prohibited Wheel










WD2088

- 1 Application: Drive Wheel for short distance on/off road use.
- 2 Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- 3 Longer Mileage, Strong Structure, Good anti-wear performance.










- Standard Wheel
- Permitted Wheel
- Prohibited Wheel




M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
A1060R01	11R22.5 148/145M	16	14.5	18.4	8.25	TL	ALL	On/Off	-	-	-	-
A1060R02	11R24.5 149/146M	16	14.5	18.4	8.25	TL	ALL	On/Off	-	-	-	-
A1060R11	295/80R22.5 152/149M	18	15.0	19.0	9.00	TL	ALL	On/Off	C	D		74
A1060R04	315/80R22.5 156/150M	20	15.0	19.0	9.00	TL	ALL	On/Off	C	D		74
A1060R03	12R22.5 152/149M	18	15.0	19.0	9.00	TL	AL	On/Off	C	D		74
A1060R05	13R22.5 156/150L	20	15.0	19.0	9.75	TL	ALL	On/Off	C	D		74

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2060R01	11R22.5 148/145M	16	20.0	25.2	6.00	TL	Drive	On/Off	-	-	-	-
D2060R06	11R24.5 149/146K	16	20.0	25.2	6.75	TL	Drive	On/Off	-	-	-	-
D2060R02	295/80R22.5 152/149K	18	20.0	25.2	6.00	TL	Drive	On/Off	D	D		75
D2060R04	315/80R22.5 156/150K	20	20.0	25.2	6.75	TL	Drive	On/Off	D	D		75
D2060R03	12R22.5 152/149K	18	20.0	25.2	6.75	TL	Drive	On/Off	D	D		75
D2060R05	13R22.5 156/150K	20	20.0	25.2	7.50	TL	Drive	On/Off	D	D		75

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D208803	11R22.5 146/143K	16	22.0	27.8	8.25	TL	Drive	Off	-	-	-	-
D208809	* 11R24.5 149/146G	16	22.0	27.8	8.25	TL	Drive	Off	-	-	-	-
D208804	295/80R22.5 152/149K	18	22.0	27.8	9.00	TL	Drive	Off	-	-	-	-
D208806	* 315/80R22.5 156/150K	20	22.0	27.8	9.00	TL	Drive	Off	-	-	-	-
D208805	12R22.5 152/149G	18	22.0	27.8	9.00	TL	Drive	Off	-	-	-	-
D208807	13R22.5 156/150G	20	22.0	27.8	9.75	TL	Drive	Off	-	-	-	-

* New Developing Sizes

The labelling information is subject to change without notice.



WH1000

- ① Application: Trailer Wheel for long distance, also can be used on Steer Wheel.
- ② Suitable for high speed on good road surface application, with excellent anti-wet property and side-slip resistance.
- ③ Longer mileage, Lower noise, Lower rolling resistance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel






WD2000




- ① Application: Drive Wheel for medium mileage loading series.
- ② Close Shoulder designs, the block pattern offer excellent drive force and good braking performance on paved road condition.
- ③ Excellent load capability, Longer mileage, Super Durability.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
H1000R01	11R22.5 148/145M	16	13.0	16.4	8.25	TL	Trailer	Highway	-	-	-	-
H1000R06	295/75R22.5 146/143M	16	11.0	14.0	9.00	TL	Trailer	Highway	-	-	-	-
H1000R04	11R24.5 149/146M	16	11.0	14.0	8.25	TL	Trailer	Highway	-	-	-	-
H1000R11	285/75R24.5 147/144M	16	11.0	14.0	8.25	TL	Trailer	Highway	-	-	-	-
H1000R07	295/80R22.5 152/149M	18	14.5	18.4	9.00	TL	Trailer	Highway	-	-	-	-
H1000R09	315/80R22.5 156/150M	20	14.5	18.4	9.00	TL	Trailer	Highway	-	-	-	-
H1000R08	12R22.5 152/149M	18	14.5	18.4	9.00	TL	Trailer	Highway	-	-	-	-
H1000R12	* 255/70R22.5 140/137M	16	11.0	14.0	7.50	TL	Trailer	Highway	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2000R02	11R22.5 148/145M	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-
D2000R06	295/75R22.5 146/143K	16	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-
D2000R04	11R24.5 149/146K	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-
D2000R08	285/75R24.5 147/144L	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-

* New Developing Sizes

The labelling information is subject to change without notice.



WINDFORCE



WH1022

- ① Application: Steer Wheel for long distance, also can be used on Trailer Wheel.
- ② Suitable for high speed on good road surface application, with excellent durability, anti-side wear performance.
- ③ Longer mileage, Lower noise, Good stone-picking prevention.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel



WD2028

- ① Application: Drive Wheel for short distance on/off road use.
- ② Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- ③ Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel






WD2048

- ① Application: Drive Wheel for short distance on/off road use.
- ② Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- ③ Longer Mileage, Strong Structure, Good anti-wear performance.






- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel




M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				dB
H1022R01	315/80R22.5 156/150M	20	15.0	19.0	9.00	TL	ALL	Highway	-	-	-	-
H1022R03	12R22.5 152/149L	18	15.0	19.0	9.00	TL	ALL	Highway	-	-	-	-
H1022R02	9.5R17.5 143/141J	18	13.0	16.4	6.75	TL	ALL	Highway	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				dB
D2028R01	315/80R22.5 156/150K	20	18.0	22.8	9.00	TL	Drive	On/Off	-	-	-	-
D2028R02	9.5R17.5 143/141J	18	15.0	19.0	6.75	TL	Drive	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				dB
D2048R02	315/80R22.5 156/150K	20	20.0	25.2	9.00	TL	Drive	On/Off	-	-	-	-
D2048R01	12R22.5 152/149L	18	20.0	25.2	9.00	TL	Drive	On/Off	-	-	-	-

* New Developing Sizes

The labelling information is subject to change without notice.



WT3020

- ❶ Application: Trailer Wheel for regional use.
- ❷ Suitable for high speed on paved road surface with excellent anti-skid-side character and durability performance.
- ❸ Excellent loading capacity, Low rolling resistance, Low noise.



● Standard Wheel
 ● Permitted Wheel
 ✗ Prohibited Wheel



WT3030






- ❶ Application: Drive Wheel for On/Off Road use.
- ❷ Suitable for mix road use and relatively poor road condition with excellent traction character.
- ❸ Excellent load capability, Longer mileage, Good anti-wearing.






● Standard Wheel
 ● Permitted Wheel
 ✗ Prohibited Wheel

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
T3020R01	385/65R22.5 160L	20	15.5	19.6	11.75	TL	Trailer	Highway	-	-	-	-
T3020R02	425/65R22.5 165K	20	15.5	19.6	13.00	TL	Trailer	Highway	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
T3030R01	* 385/55R22.5 160K	20	16.0	20.2	12.25	TL	All	On/Off	-	-	-	-
T3030R02	* 385/65R22.5 160K	20	16.0	20.2	11.75	TL	All	On/Off	-	-	-	-
T3030R03	* 425/65R22.5 165K	20	16.0	20.2	13.00	TL	All	On/Off	-	-	-	-

* New Developing Sizes

The labelling information is subject to change without notice.



WH3060

NEW

- ① Application: Steer Wheel for long distance, also can be used as All Position pattern.
- ② New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- ③ Heavy loading capacity, Low heat build-up, High speed and Low noise.



● Standard Wheel ● Permitted Wheel ⊗ Prohibited Wheel



WD3080




NEW

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.






● Standard Wheel ● Permitted Wheel ⊗ Prohibited Wheel

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
H3060R01	* 215/75R17.5 128/126M	16	12.0	15.0	6.00	TL	All	Highway	-	-	-	-
H3060R02	* 225/75R17.5 129/127M	16	12.5	15.8	6.75	TL	All	Highway	-	-	-	-
H3060R03	* 235/75R17.5 132/130M	16	12.5	15.8	6.75	TL	All	Highway	-	-	-	-
H3060R04	* 245/70R17.5 136/134M	16	12.5	15.8	7.50	TL	All	Highway	-	-	-	-
H3060R05	* 245/70R19.5 136/134M	16	12.5	15.8	7.50	TL	All	Highway	-	-	-	-
H3060R06	* 265/70R19.5 140/138M	16	12.5	15.8	7.50	TL	All	Highway	-	-	-	-
H3060R07	* 285/70R19.5 146/144M	16	13.0	16.4	8.25	TL	All	Highway	-	-	-	-
H3060R08	* 305/70R19.5 148/145M	16	14.0	17.6	9.00	TL	All	Highway	-	-	-	-
H3060R09	* 11R22.5 148/145M	16	14.5	18.4	8.25	TL	All	Highway	-	-	-	-
H3060R10	* 12R22.5 152/149M	18	15.0	19.0	9.00	TL	All	Highway	-	-	-	-
H3060R11	* 295/80R22.5 154/149M	18	15.5	19.6	9.00	TL	All	Highway	-	-	-	-
H3060R12	* 315/80R22.5 157/154M	20	15.0	19.0	9.00	TL	All	Highway	-	-	-	-
H3060R13	* 315/70R22.5 156/150M	20	15.0	19.0	9.00	TL	All	Highway	-	-	-	-
H3060R14	* 315/60R22.5 154/148M	18	15.0	19.0	9.00	TL	All	Highway	-	-	-	-

M+S

	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D3080R01	* 215/75R17.5 128/126M	16	15.0	19.0	6.00	TL	Drive	Highway	-	-	-	-
D3080R02	* 225/75R17.5 129/127M	16	15.5	19.6	6.75	TL	Drive	Highway	-	-	-	-
D3080R03	* 235/75R17.5 132/130M	16	15.5	19.6	6.75	TL	Drive	Highway	-	-	-	-
D3080R04	* 245/70R17.5 136/134M	16	15.5	19.6	7.50	TL	Drive	Highway	-	-	-	-
D3080R05	* 245/70R19.5 136/134M	16	15.5	19.6	7.50	TL	Drive	Highway	-	-	-	-
D3080R06	* 265/70R19.5 140/138M	16	15.5	19.6	7.50	TL	Drive	Highway	-	-	-	-
D3080R07	* 285/70R19.5 146/144M	16	16.0	20.2	8.25	TL	Drive	Highway	-	-	-	-
D3080R08	* 305/70R19.5 148/145M	16	18.0	22.8	9.00	TL	Drive	Highway	-	-	-	-
D3080R09	* 11R22.5 148/145M	16	20.0	25.2	8.25	TL	Drive	Highway	-	-	-	-
D3080R10	* 12R22.5 152/149M	18	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R11	* 295/80R22.5 154/149M	18	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R12	* 315/80R22.5 157/154M	20	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R13	* 315/70R22.5 156/150M	20	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R14	* 315/60R22.5 154/148M	18	20.0	25.2	9.00	TL	Drive	Highway	-	-	-	-

* New Developing Sizes.

The labelling information is subject to change without notice.



WA1060

- ① Application: All Position Wheels for On/Off use.
- ② Mixed pattern, Suitable for mixed road surface and relatively poor road condition with sideslip resistance.
- ③ Excellent crack & tear resistance, High speed, Long mileage.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel



WD2062

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel






WD2062+

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.






- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel




M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
A1060R15	7.00R16LT 118/114L	14	12.0	15.0	5.50	TT	ALL	On/Off	-	-	-	-
A1060R13	7.50R16LT 122/118L	14	13.0	16.4	6.50	TT	ALL	On/Off	-	-	-	-
A1060R14	8.25R16LT 128/124K	16	13.0	16.4	6.50	TT	ALL	On/Off	-	-	-	-
A1060R06	9.00R20 144/142K	16	15.5	19.6	7.00	TT	ALL	On/Off	-	-	-	-
A1060R07	10.00R20 149/146K	18	16.0	20.2	7.50	TT	ALL	On/Off	-	-	-	-
A1060R08	11.00R20 152/149K	18	16.0	20.2	8.00	TT	ALL	On/Off	-	-	-	-
A1060R09	12.00R20 156/153K	20	16.0	20.2	8.50	TT	ALL	On/Off	-	-	-	-
A1060R10	12.00R24 160/157K	20	15.0	20.2	8.50	TT	ALL	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2062R07	7.00R16LT 118/114K	14	14.5	18.4	5.50	TT	Drive	On/Off	-	-	-	-
D2062R05	7.50R16LT 122/118K	14	14.5	18.4	6.50	TT	Drive	On/Off	-	-	-	-
D2062R06	8.25R16LT 128/124K	16	14.5	18.4	6.50	TT	Drive	On/Off	-	-	-	-
D2062R01	9.00R20 144/142J	16	18.0	22.8	7.00	TT	Drive	On/Off	-	-	-	-
D2062R02	10.00R20 149/146K	18	18.0	22.8	7.50	TT	Drive	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth		Standard Rim	Tubeless/Tube	Rim position	Application				dB
			MM	1/32"								
D2062R03+	11.00R20 152/149K	18	18.5	23.4	8.00	TT	Drive	On/Off	-	-	-	-
D2060R04+	12.00R20 156/153K	20	19.5	24.6	8.50	TT	Drive	On/Off	-	-	-	-

* New Developing Sizes

The labelling information is subject to change without notice.



WINDFORCE



WA1066

- ① Application: All Position Wheels for On/Off use.
- ② Mixed pattern, Suitable for mixed road surface and relatively poor road condition with high loading capability.
- ③ Excellent crack & tear resistance, Good anti-uneven wear character.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel



WD2066

- ① Application: Drive Wheel for short distance on/off road use.
- ② Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- ③ Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel







WD2088

- ① Application: Drive Wheel for short distance on mining and construction areas.
- ② Suitable for low speed ride on bad road condition, specially for mining area, with powerful grip and high loading ability.
- ③ Longer Mileage, Strong Structure, Good anti-wear performance.







- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel





M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
A1066R03	9.00R20 144/142K	16	15.5	19.6	7.00	TT	ALL	On/Off	-	-	-	-
A1066R04	10.00R20 149/146K	18	16.0	20.2	7.50	TT	ALL	On/Off	-	-	-	-
A1066R01	11.00R20 152/149K	18	16.0	20.2	8.00	TT	ALL	On/Off	-	-	-	-
A1066R02	12.00R20 156/153K	20	16.0	20.2	8.50	TT	ALL	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
D2066R01	11.00R20 152/149J	18	18.5	23.4	8.00	TT	Drive	On/Off	-	-	-	-
D2066R02	12.00R20 156/153J	20	19.5	24.6	8.50	TT	Drive	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
D2088R01	11.00R20 152/149G	18	21.0	26.4	8.00	TT	Drive	Off	-	-	-	-
D2088R02	12.00R20 156/153G	20	22.0	27.8	8.50	TT	Drive	Off	-	-	-	-
D2088R08	12.00R24 160/157G	20	22.0	27.8	8.50	TT	Drive	Off	-	-	-	-

* New Developing Sizes.

The labelling information is subject to change without notice.



WINDFORCE



WA1088

- ① Application: Steer Wheel for long distance, also can be used as All Position pattern.
- ② New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- ③ Heavy loading capacity, Low heat build-up, High speed and Low noise.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel



WD2040

- ① Application: Drive Wheel for short distance on/off road use.
- ② Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- ③ Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel






WD2020

- ① Application: Drive Wheel for medium mileage load series.
- ② Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- ③ Excellent load capability, Longer mileage, Super Durability.






- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel





M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/Tube	Rim position	Application				dB
A1088R03	11.00R20 152/149K	18	16.5 20.8	8.00	TT	All	Highway	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/Tube	Rim position	Application				dB
D2040R01	10.00R20 149/146K	18	20.0 25.2	7.50	TT	Drive	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/Tube	Rim position	Application				dB
D2020R20	10.00R20 149/146K	18	20.0 25.2	7.50	TT	Drive	Highway	D	C		75

* New Developing Sizes.

The labelling information is subject to change without notice.



WA1068

- ❶ Application: All Position Wheels for long mileage load series.
- ❷ New designed pattern, Suitable for well paved road condition with excellent durability.
- ❸ Standard load, Low heat build-up, High speed.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel



WD2068

- ❶ Application: Drive Wheel for short distance on/off road use.
- ❷ Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- ❸ Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel







WA1062+

- ❶ Application: All Position Wheels for long mileage load series.
- ❷ New designed pattern, Suitable for well paved road condition with excellent durability.
- ❸ Standard load, Low heat build-up, High speed.







- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel





M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
A1068R01	12.00R24 160/157K	20	16.0	20.2	8.50	TT	ALL	Highway	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
D2068R01	12.00R24 160/157K	20	16.0	20.8	8.50	TT	Drive	On/Off	-	-	-	-

M+S

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"		Standard Rim	Tubeless/Tube	Rim position	Application				
D1062R01+	12.00R24 160/157K	20	16.0	20.8	8.50	TT	ALL	Highway	-	-	-	-

* New Developing Sizes.

The labelling information is subject to change without notice.