

product catalogue

SEHA[®]
brand tyres

best fit for your needs





SEHA[®]
brand tyres

best fit for your needs

AGRICULTURAL



KNK 30

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
31020	6.00-16	6	TUBETYPE	4.50E	165	735	88	A6	560	48	2242	335
31030	6.00-16	8	TUBETYPE	4.50E	165	735	93	A6	650	48	2242	335
32020	6.50-16	6	TUBETYPE	4.50E	175	760	91	A6	615	45	2318	345
32030	6.50-16	8	TUBETYPE	4.50E	175	760	97	A6	730	54	2318	345
34020	7.50-16	6	TUBETYPE	5.50F	205	805	98	A6	750	41	2455	363
34030	7.50-16	8	TUBETYPE	5.50F	205	805	103	A6	875	54	2455	363



KNK 32

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
34120	7.50-16	6	TUBETYPE	5.50F	205	805	98	A6	750	41	2455	363
34130	7.50-16	8	TUBETYPE	5.50F	205	805	103	A6	875	54	2455	363
35130	7.50-18	8	TUBETYPE	5.50F	205	860	106	A6	950	54	2623	390
35520	6.50-20	6	TUBETYPE	5.00F	175	865	97	A6	730	45	2638	397
35530	6.50-20	8	TUBETYPE	5.00F	175	865	102	A6	850	54	2638	397
36020	7.50-20	6	TUBETYPE	5.50F	205	915	103	A6	875	40	2791	417
36030	7.50-20	8	TUBETYPE	5.50F	205	915	108	A6	1000	49	2791	417



KNK 33

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
31320	6.00-16	6	TUBETYPE	4.50E	165	735	88	A6	560	48	2242	335
31330	6.00-16	8	TUBETYPE	4.50E	165	735	93	A6	650	48	2242	335
32320	6.50-16	6	TUBETYPE	4.50E	175	760	91	A6	615	45	2318	345
32330	6.50-16	8	TUBETYPE	4.50E	175	760	97	A6	730	54	2318	345
34720	7.50-16	6	TUBETYPE	5.50F	205	805	98	A6	750	41	2455	363
34730	7.50-16	8	TUBETYPE	5.50F	205	805	103	A6	875	54	2455	363
35420	6.00-19	6	TUBETYPE	4.50E	165	814	93	A6	650	48	2483	374



KNK 35

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
30520	5.50-16	6	TUBETYPE	4.00E	150	710	86	A6	530	54	2166	325
30530	5.50-16	8	TUBETYPE	4.00E	150	710	91	A6	615	54	2166	325
31120	6.00-16	6	TUBETYPE	4.50E	165	735	88	A6	560	48	2242	335
31130	6.00-16	8	TUBETYPE	4.50E	165	735	93	A6	650	48	2242	335
32120	6.50-16	6	TUBETYPE	4.50E	175	760	91	A6	615	45	2318	345
32130	6.50-16	8	TUBETYPE	4.50E	175	760	97	A6	730	54	2318	345
34320	7.50-16	6	TUBETYPE	5.50F	205	805	98	A6	750	41	2455	363
34330	7.50-16	8	TUBETYPE	5.50F	205	805	103	A6	875	54	2455	363
34630	9.00-16	8	TUBETYPE	W8	234	855	111	A6	1090	45	2608	383
34830	10.00-16	8	TUBETYPE	W8	274	895	115	A6	1215	41	2730	399
34930	11.00-16	8	TUBETYPE	10	315	965	118	A6	1320	36	2943	427
35020	7.50-18	6	TUBETYPE	5.50F	205	860	101	A6	825	41	2623	390
35030	7.50-18	8	TUBETYPE	5.50F	205	860	106	A6	950	54	2623	390



KNK 50

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
30030	7.50-15	8	TUBETYPE	5,50E	205	780	99	A6	775	52	2379	350
31220	6.00-16	6	TUBETYPE	4,50E	165	735	88	A6	560	48	2242	335
31230	6.00-16	8	TUBETYPE	4,50E	165	735	93	A6	650	48	2242	335
32220	6.50-16	6	TUBETYPE	4,50E	175	760	91	A6	615	45	2318	345
32230	6.50-16	8	TUBETYPE	4,50E	175	760	97	A6	730	54	2318	345
34220	7.50-16	6	TUBETYPE	5,50F	205	805	98	A6	750	41	2455	363
34230	7.50-16	8	TUBETYPE	5,50F	205	805	103	A6	875	54	2455	363
34420	280/70-16	6	TUBELESS/TUBETYPE	W9	282	798	102	A6	850	23	2434	360
34430	280/70-16	8	TUBELESS/TUBETYPE	W9	282	798	112	A6	1120	35	2434	360
35230	7.50-18	8	TUBETYPE	5,50F	205	860	106	A6	950	54	2623	390
35620	280/70-18	6	TUBELESS	W9	282	849	104	A6	900	23	2589	385
35630	280/70-18	8	TUBELESS	W9	282	849	114	A6	1180	35	2589	385
36230	7.50-20	8	TUBETYPE	5,50F	205	915	108	A6	1000	49	2791	417
36630	9.5-20	8	TUBELESS/TUBETYPE	W8	241	940	106	A6	950	35	2867	427
36830	11.2-20	8	TUBELESS/TUBETYPE	W10	285	1005	113	A6	1150	38	3065	453



Special design for farm tractor as rear tyre and also as front tyre and as front tyre for combined harvesters.

Tread pattern provides very good tracking on the field and also self-cleaning ability.

The thick lug with special compound provides improved tyre mileage and uniform wear.



KNK 50

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
50020	8.3-24	6	TUBETYPE	W7	210	1009	105	A6	925	30	3077	465
50030	8.3-24	8	TUBETYPE	W7	210	1009	108	A6	1000	35	3077	465
51020	9.50-24	6	TUBETYPE	W8	241	1050	110	A6	1060	26	3203	481
51030	9.50-24	8	TUBETYPE	W8	241	1050	116	A6	1250	34	3203	481
51120	11.2/10-24	6	TUBETYPE	W10	284	1105	110	A6	1060	26	3370	503
51130	11.2/10-24	8	TUBETYPE	W10	284	1105	116	A6	1250	34	3370	503
51150	11.2/10-24	12	TUBETYPE	W10	284	1105	122	A6	1500	40	3370	503
51220	12.4/11-24	6	TUBETYPE	W11,DW11	315	1160	115	A6	1215	24	3538	525
51230	12.4/11-24	8	TUBETYPE	W11,DW11	315	1160	118	A6	1320	29	3538	525
51250	12.4/11-24	12	TUBETYPE	W11,DW11	315	1160	124	A6	1600	35	3538	525
51320	13.6/12-24	6	TUBETYPE	W12,DW12	345	1210	120	A6	1400	22	3691	545
51330	13.6/12-24	8	TUBETYPE	W12,DW12	345	1210	123	A6	1550	28	3691	545
51350	13.6/12-24	12	TUBETYPE	W12,DW12	345	1210	129	A6	1850	34	3691	545
51420	14.9/13-24	6	TUBETYPE	W13	378	1265	125	A6	1650	20	3858	567
51430	14.9/13-24	8	TUBETYPE	W13	378	1265	128	A6	1800	26	3858	567
51440	14.9/13-24	10	TUBETYPE	W13	378	1265	131	A6	1950	30	3858	567
51460	14.9/13-24	14	TUBETYPE	W13	378	1265	137	A6	2300	38	3858	567
51840	14.9/13-26	10	TUBETYPE	W13	378	1315	133	A6	2060	30	4011	592
51860	14.9/13-26	14	TUBETYPE	W13	378	1315	140	A6	2500	39	4011	592
51540	18.4/15-26	10	TUBETYPE	W15L,W16L	467	1461	142	A6	2650	26	4456	650
51560	18.4/15-26	14	TUBETYPE	W15L,W16L	467	1461	150	A6	3350	40	4456	650
51950	15.5/80-24	12	TUBELESS	W12	394	1260	157	A6	4125	44	3843	565
51970	15.5/80-24	16	TUBELESS	W12	394	1260	163	A6	4875	58	3843	565
52020	11.2/10-28	6	TUBETYPE	W10	284	1205	112	A6	1120	26	3675	553
52030	11.2/10-28	8	TUBETYPE	W10	284	1205	118	A6	1320	34	3675	553
52120	12.4/11-28	6	TUBETYPE	W11	315	1260	117	A6	1285	25	3843	575
52130	12.4/11-28	8	TUBETYPE	W11	315	1260	125	A6	1650	30	3843	575
52220	13.6/12-28	6	TUBETYPE	W12,DW12	345	1310	121	A6	1450	23	3996	595
52230	13.6/12-28	8	TUBETYPE	W12,DW12	345	1310	125	A6	1650	29	3996	595
52320	14.9/13-28	6	TUBETYPE	W13,DW13	378	1365	125	A6	1650	20	4163	617
52330	14.9/13-28	8	TUBETYPE	W13,DW13	378	1365	130	A6	1900	26	4163	617
52340	14.9/13-28	10	TUBETYPE	W13,DW13	378	1365	135	A6	2180	30	4163	617
52360	14.9/13-28	14	TUBETYPE	W13,DW13	378	1365	143	A6	2725	40	4163	617
52530	16.9/14-28	8	TUBETYPE	W14L	429	1435	135	A6	2180	24	4377	645
52540	16.9/14-28	10	TUBETYPE	W14L	429	1435	139	A6	2430	29	4377	645
52560	16.9/14-28	14	TUBETYPE	W14L	429	1435	143	A6	2725	34	4377	645
53030	14.9/13-30	8	TUBETYPE	W13	378	1415	132	A6	2000	26	4316	642
53040	14.9/13-30	10	TUBETYPE	W13	378	1415	136	A6	2240	29	4316	642
53130	16.9/14-30	8	TUBETYPE	W15L	429	1485	137	A6	2300	25	4529	670
53140	16.9/14-30	10	TUBETYPE	W15L	429	1485	144	A6	2800	28	4529	670
53160	16.9/14-30	14	TUBETYPE	W15L	429	1485	150	A6	3350	34	4529	670
53230	18.4/15-30	8	TUBETYPE	W16L	467	1550	139	A6	2430	20	4728	696
53240	18.4/15-30	10	TUBETYPE	W16L	467	1550	145	A6	2900	26	4728	696
53260	18.4/15-30	14	TUBETYPE	W16L	467	1550	154	A6	3750	40	4728	696
54120	8.3-32	6	TUBETYPE	W7	211	1195	105	A6	925	35	3645	559
54130	8.3-32	8	TUBETYPE	W7	211	1195	111	A6	1090	46	3645	559
54170	8.3-32	8	TUBELESS	W7	211	1195	111	A6	1090	46	3645	559
54220	9.5-32	6	TUBETYPE	W8	241	1250	109	A6	1030	30	3813	581
54230	9.5-32	8	TUBETYPE	W8	241	1250	115	A6	1215	39	3813	581
54270	9.5-32	8	TUBELESS	W8	241	1250	115	A6	1215	39	3813	581
54320	12.4-32	6	TUBETYPE	W11	315	1360	119	A6	1360	24	4148	625
54330	12.4-32	8	TUBETYPE	W11	315	1360	125	A6	1650	32	4148	625
55130	16.9/14-34	8	TUBETYPE	W15L	429	1585	139	A6	2430	24	4834	720
55140	16.9/14-34	10	TUBETYPE	W15L	429	1585	142	A6	2650	29	4834	720
55160	16.9/14-34	14	TUBETYPE	W15L	429	1585	148	A6	3150	37	4834	720
55240	18.4/15-34	10	TUBETYPE	W16L	467	1650	146	A6	3000	26	5033	746
55260	18.4/15-34	14	TUBETYPE	W16L	467	1650	153	A6	3650	36	5033	746
56020	12.4/11-36	6	TUBETYPE	W11,DW11	315	1465	121	A6	1450	24	4468	677
56030	12.4/11-36	8	TUBETYPE	W11,DW11	315	1465	126	A6	1700	29	4468	677
56120	13.6/12-36	6	TUBETYPE	W12,DW12	345	1515	125	A6	1650	23	4621	697



KNK 48

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
4605 0	10.5/80 -18	12	TUBETYPE	9	274	885	135	A8	2180	65	2699	400
4626 0	12.5/80 -18	14	TUBETYPE	9	308	965	144	A8	2800	63	2943	432
4647 0	13.0/65 -18	16	TUBETYPE	11	336	890	144	A8	2800	66	2715	402



KNK 50

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
51760	23.1-26	14	TUBELESS	DW20A	587	1605	156	A6	4000	29	4895	708
51770	23.1-26	16	TUBELESS	DW20A	587	1605	159	A6	4375	33	4895	708
51780	23.1-26	18	TUBELESS	DW20A	587	1605	162	A6	4750	37	4895	708
53570	23.1-30	16	TUBELESS	DW20A	587	1715	157	A6	4125	32	5231	762
53580	23.1-30	18	TUBELESS	DW20A	587	1715	160	A6	4500	36	5231	762
57570	20.8-38	16	TUBETYPE	W18L	528	1840	162	A6	4750	39	5612	833
57670	20.8-38	16	TUBELESS	W18L	528	1840	162	A6	4750	39	5612	833
67270	16.9/14-30	16	TUBETYPE	W15L	429	1485	154	A6	3750	38	4529	670
67370	18.4/15-30	16	TUBETYPE	W16L	467	1550	158	A6	4250	45	4728	696
55270	18.4/15-34	16	TUBETYPE	W16L	467	1650	159	A6	4375	45	5033	746



KNK 50

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
18130	6.50/80 -15	6	TUBETYPE	5,0	163	663	86	A6	530	52	2022	303



KNK 52

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
15010	4,50-10	4	TUBETYPE	3,00D	124	490	49	A6	185	30	1495	221
16110	5,00-12	4	TUBETYPE	3,50D	145	580	62	A6	265	32	1769	262
17320	7,00-12	6	TUBETYPE	4,25E	200	683	83	A6	487	36	2083	304
17520	6.50/80 -13	6	TUBETYPE	5,00F	170	640	82	A6	475	52	1952	289



KNK 54

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
1702 0	6.50/80 -12	6	TUBETYPE	5J	163	588	80	A6	450	52	1793	266



KNK 140

Code	Tyre Size	PR	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)		
1802 0	5.00 -15	6	TUBETYPE	3,50D	145	655	76	A6	400	50	1998	300



SEHA[®]
brand tyres

best fit for your needs

LIGHT TRUCK



KNK 20

Code	Tyre Size	(PR)	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Tyre Pressure (Psi)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			2 Wheel Axle Load (kg)	4 Wheel Axle Load (kg)			
21030	6.50-14C	8	TUBETYPE	5,0J	171	647	97/95	L	1460	2760	65	1973	287
21440	7.50-15C	10	TUBETYPE	6,0G	235	789	114/112	L	2360	4480	76	2406	344
22040	6.50-16C	10	TUBETYPE	4,50E-SDC	176	748	108/107	L	2000	3900	73	2281	331
23040	7.00-16C	10	TUBETYPE	5,50F-SDC	198	785	113/112	L	2300	4480	76	2394	345
24050	7.50-16C	12	TUBETYPE	6,0G-SDC	210	810	121/120	L	2900	5600	94	2471	355



KNK 24

Code	Tyre Size	(PR)	Tubeless Tubetype	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure		Tyre Pressure (Psi)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
					Section Width (mm)	Overall Diameter (mm)			2 Wheel Axle Load (kg)	4 Wheel Axle Load (kg)			
24150	7.50-16C	12	TUBETYPE	6,0G-SDC	210	810	121/120	L	2900	5600	94	2471	355